

Model	Uses FODO	Has quadrupoles in carrier pipe
Tweaked Baseline	No	No
FODO	Yes	Yes


Table 1: Summary of the key features of the beamline models compared in this note.

“Tweaked Baseline”



1 mm by 1 μ radian and $\Delta p/p = 10^{-4}$.
Horizontal envelope is blue.

“FODO”



1 mm by 1 μ radian and $\Delta p/p = 10^{-4}$.
Horizontal envelope is blue.

Model	Horizontal	Vertical
	$[\pi \cdot mm \cdot mr]$	$[\pi \cdot mm \cdot mr]$
Tweaked Baseline	110	444
FODO	1116	1321

Table 2: Normalized admittance, in $\pi \cdot mm \cdot mr$, of each model. Admittance of each plane is calculated independently.


Model	Horizontal [$\pi \cdot mm \cdot mr$]	Vertical [$\pi \cdot mm \cdot mr$]	Aperture [mm^2]
Tweaked Baseline	35	200	7000
FODO	648	707	458136
FODO	500	500	250000

Table 3: Normalized admittance, including $\delta p/p = \pm 1.1 \times 10^{-3}$, for each model. Horizontal and vertical phase space are populated simultaneously, though uncorrelated. “FODO” is shown a second time with the admittance truncated to the emittance of the Main Injector.

Model	$\pm\delta p/p$
Tweaked Baseline	2.3×10^{-3}
FODO	3.8×10^{-3}


Table 4: Maximum momentum acceptance at 40π .

“Tweaked Baseline”





$$40\pi, \Delta p/p(2\sigma) = 14.0 \times 10^{-4}$$


“FODO”




$$40\pi, \Delta p/p(2\sigma) = 14.0 \times 10^{-4}$$









TRK
02Apr02
NuMI Review